


MEC TARN 3

This booklet tells you how to prepare, assemble, and maintain your new tent; please keep it for future reference. Set up your tent at home before your first trip; this will allow you to inspect it for any manufacturing defects, check that all parts are present, and learn the assembly procedure with minimal stress on the tent and on you.



Your Tarn 3 tent package includes:

- Tent body
- Tent fly
- Three aluminum poles
- Aluminum stakes and nylon guylines
- Aluminum pole repair sleeve
- Tent sack and pole sack



TARN 3 Height inside 1.3m



SEAM SEALING

The seams of your tent have been waterproof taped on all exposed seams. All features, such as Velcro® pole anchors and door tiebacks, have been welded onto the inside of the fly to avoid any small leak points. However, for extremely wet and windy conditions, you may want to re-seal selected parts of your tent. These include parts of the inner tent where condensation or windblown rain could potentially wick through, such as lantern loops or pole clip suspension points. You may also wish to seal the “in” side of any untaped floor seams exposed to ground moisture or rainfall. For seam sealing and tent repairs, we recommend a quality after-market polyurethane sealer such as McNett Seam Grip®.

Work in a well-ventilated area to avoid inhaling sealant vapours. For complete sealing, evenly apply only the minimum required amount of sealant into needle holes, thread, and fabric joints. Allow to dry and cure overnight. McNett sealants (Seam Grip, and similar) cure more quickly in a moist or humid environment. Before packing the tent for the first time, dust newly sealed areas with talcum powder or spray them with 303™ Protectant; freshly cured sealer can bond to itself even when dry. If the tent is used hard and often you may need to reapply seam sealer in high-wear areas.



SITE PREPARATION

Remove sharp objects that might puncture the tent floor.

A ground sheet beneath the tent is not necessary for waterproofness, but it will reduce long-term wear on the tent floor. A ground sheet should be cut or folded smaller than the tent floor to prevent water pooling between the floor and the ground sheet. Another light and convenient option is MEC's custom-made, coated nylon Footprint.

In winter conditions, we recommend digging out a platform with surrounding walls. To avoid melting depressions in the snow under the tent, pack the snow down solidly by ski or foot.



SET-UP

A note about shock-corded poles

Shockcord (bungee cord) is meant to keep pole sections in the proper order—not as an automatic assembly mechanism for poles. Do not hold one section while whipping the rest of the pole back and forth, or toss the poles into the air; either procedure excessively stresses the pole joints and shockcord. Instead, fit poles together section by section, making sure that each piece slides completely into the next. Forcing an improperly assembled pole into place can damage the pole and/or the tent body and fly.

Assembling the Tent

1 *Assemble all poles carefully as described in the previous paragraph.* You will have two side arch poles of equal length and one shorter front arch pole with an angled section in the middle.

2 *Lay the tent body out flat, and unzip the door.* In windy conditions, peg out all floor corners before proceeding.

3 *Lay the two equal length side arch poles on top of the tent body, crossing them in the centre to form an “X.”*

4 The plastic pole clips on the tent body are divided into three sets; each set is identified by a separate colour of webbing loops. Each clip set follows a seam line so that each pole will run parallel to one seam once it is attached.

Start by the door at one front corner. Clip all of one colour set of pole clips to one of the side arch poles, following the seam line to the diagonally opposite back corner. Do the same with the other side arch pole, using all of another colour set of clips.

5 There are webbing tabs with grommets at all six corners of the tent body. The webbing colours correspond to the appropriate pole clip colours. Each webbing tab has two grommets so that you can increase or decrease the tautness of the tent to allow for the fabric slackening caused by changes in humidity.

Carefully fit the pole ends into the grommets at the four outside corners of the tent body.

6 At the front of the tent, slip the front arch pole over the side arch poles. Fit the pole ends into the grommets at the side corners of the tent. Attach the remaining clips to the front arch pole. For maximum stability, attach the bottommost clip on each side to the front arch pole just above the point where it crosses over the side poles. This pulls the poles closer, allowing them to brace against one another.



7 Spread the fly over the tent body with the webbing colours on the fly corners matching the webbing colours on the tent floor corners (the scooped vent on the fly goes in front of the door in the tent body).

8 On the underside of the fly are four Velcro® wrap-ties.

Attach all the wrap-ties. It is easiest to attach them in the following order:

One wrap-tie goes around the centre of the front arch pole, at its highest point. Two more wrap-ties go around the two junctions where the front arch pole and the longer side poles cross. The final wrap-tie goes around the junction of the two long poles at the back of the tent. Note: at these pole junctions, fasten the wrap-ties around both poles as tightly as possible; this will maximize the tent's strength by bracing the poles against each other. *To do this: wrap the longer Velcro tab horizontally twice around both poles, pull on the tab end to cinch it tight, then secure it by folding the shorter Velcro tab over it.*

9 Fit all six webbing tabs onto the appropriate pole tips, over the webbing grommets from the tent body as shown in figures A and B. Fold the tabs under the body of the tent as you go.



The basic set-up is now complete.

Staking and Tensioning the Tent

Even freestanding tents should be pegged to avoid them blowing away and to permit proper ventilation. At a minimum, peg out the two back corners of the tent and the two front corners of the vestibule.

The Tarn 3 has anchor loops and external guy points for even more secure anchoring in windy conditions. First anchor the corners of the floor with pegs. If you have not already done so, attach the Velcro wrap-ties on the

underside of the fly to the poles (see Step 7, above.) Guy out the two guypoints corresponding to these wrap-ties if necessary. For additional stability, peg out the pullouts at the base of the fly sidewalls.

The Tarn 3 is designed for lightweight, compact, three-season performance. Keep this in mind when selecting and preparing a tent site: a little shelter as provided by trees, rock, or snow walls will make for a quieter night's sleep under windy conditions.

Anchoring the Tent

The #7001-T6 aluminum stakes included with the tent are suitable for general use on relatively soft ground. However, in very hard-packed ground you will need stronger (and heavier!) stakes that can withstand the force needed to drive them in. On snow, sand, or other loose-packed surfaces, wider T-Stakes or aluminum snow stakes will hold better; these stakes hold best buried horizontally. You can also improvise with other "stakes" (hiking staffs, ice axes, branches, rocks, trees), using the tent's stake loops or cord as required.

When packing for your trip, consider the conditions you'll likely encounter and what sort of anchors you'll require. You can often leave several of the supplied pegs at home and replace them with improvised anchors, thereby saving weight and space in your pack.

Ventilating the Tent

Proper ventilation is the key to minimizing condensation in any tent. Keep fabric doors open as widely as the prevailing weather permits. If bugs or drafts aren't a problem, leave mesh doors open too. Crack each door open from the top down; warm, moist air rises and will escape through high openings. If the design of your tent allows for it, have openings at both ends or both sides of the tent to allow air to flow through for best ventilation. On very hot nights, when you are confident there will be no rain or dewfall, you can leave the flysheet off and use the inner tent alone as a "bug tent."

Disassembling the Tent

The most important consideration in taking down a tent is not to stress the poles and fabrics. First, disconnect guylines and release the tension from the tent. Next, release all the poles. If your tent has pole sleeves, push the poles out of the sleeves instead of pulling them out. To minimize the stress on the bungee cord in the poles and to speed disassembly, fold each pole in half first, and then fold down towards the outsides, two sections at a time.

Packing the Tent

If possible, fold and roll the tent rather than stuffing it into its sack—rolling makes a smaller package, and causes fewer creases in the polyurethane coating. The tent and poles may be carried separately for easier packing or load sharing. There are two drawcords on the tent sack. Use the lower one when carrying the tent separately from the poles; this makes a shorter package that fits sideways into a pack. If carrying the pole sack on the outside of a pack, securely attach the drawcord to the pack to avoid loss.

A pole tip: The angled middle section of the front arch pole has one longer and one shorter adjoining section. If you leave the angled section plugged into the shorter section rather than into the longer one, the final pole package will be shorter. Experiment to see which side is the correct one to unplug. You may wish to mark the shorter section with a piece of tape as a reminder.



CARE AND MAINTENANCE

Protecting the Tent

Ultraviolet damage is the single largest hazard your tent faces in its lifetime. Fabrics should not be exposed to sunlight for extended periods of time; this will eventually result in colour fading and fabric failure. The uncoated fabrics of the tent canopy are most susceptible to damage from UV and should be covered by the more durable fly. If extended exposure is unavoidable, cover the tent with a tarp or a sheet of nylon.

Lighting your Tent

Using a candle lantern in a tent carries definite risks. Never leave a candle lantern burning unattended; always watch for fire hazard from overheating fabrics or spilling wax. Spilling wax can be dangerous, particularly to eyes and other sensitive areas. It is your responsibility to use candle lanterns wisely and with extreme caution: we do not endorse the use of any flame or heat source in a tent. Cooking in a tent is strongly discouraged because of fire hazards and carbon monoxide inhalation risks. Unlike campfire smoke and other fumes, which cause you to gasp for air, **carbon monoxide can render you unconscious without any warning.** ☠

Food in Tents

Mop up spills promptly with water. Many foods, particularly acidic ones like fruit or juices, can weaken synthetic fabrics over time. In any case it is best to eat and store food away from a tent to avoid attracting animals.

Cleaning

Clean the tent by hand while it is set up, using a sponge, a mild non-detergent soap, and warm water. Rinse thoroughly. Do not dry clean, machine wash, or machine dry. Stubborn stains like tar can be left in place and dusted with talcum powder to prevent transfer to other areas of the tent in storage. After cleaning, a spray-on water repellent designed for synthetic fabrics may be applied to the flysheet if surface water repellency is weakening. (This is apparent when water droplets no longer bead up on the fabric.)

If the poles are exposed to salt or salt water, rinse them in fresh water and allow them to dry before storing. (While aluminum does not rust, it can become brittle through unseen corrosion over time.)

Lubricating the Poles

Occasionally apply a light coating of a silicone-based lubricant like 303™ Protectant to the tent pole connections. If the poles are used extensively in marine environments, treat them more frequently.

Storing your Tent

Dry the tent and poles completely before storage to avoid mildew or hidden pole corrosion. Store in a cool, dry place out of direct light.

Mildewed tents can be cleaned as described above, but there is no way to remove the dark stains without damaging the fabric. Mildew will probably take some time to affect the waterproof coatings, so the tent should still be usable.



REPAIRING YOUR TENT

Fabric Tears

Watertight repairs to rips can be made with seam sealant such as McNett Freesole™, Aquaseal™, or Seam Grip®. For tears shorter than about 1.5cm (1/2in.), apply duct tape to one side and sealant to the other. On longer tears, apply duct tape to one side of the tear and, on the other side, a patch of no-see-um netting that extends about 6-12mm (1/4-1/2in.) beyond each edge of the tear. Use oval or circular patches (rounded edges are less likely to peel away than sharp corners). Cover the patch thoroughly in sealant. Once the sealant is completely dry, the duct tape can be removed from small and large repairs alike.

For longer trips, we recommend taking an expedition sewing kit and extra nylon, webbing, a spare pole section, and narrow-diameter (2.5mm) tent pole shockcord. Coghlan's Seam Saturant or the like will prevent wicking through a tent fly via seams or webbing.

Fixing a Pole in the Field

Slip the pole repair sleeve over one pole end. Slide the sleeve along until it is centred over the break in the pole, then wrap it into place with duct tape. Be careful not to damage the tent fabrics when removing the damaged pole.

Replacing a Broken Pole Section

The MEC Grip-Tip™ pole tips are press-fitted into place. Carefully tug out the pole end tip nearest to the broken section. Being mindful of how to retie it later, untie the end tip. Slide pole sections off the cord until you reach the damaged section. Remove the broken piece, being careful not to damage the shockcord. Thread on a new section of appropriate length and diameter, followed by the other sections, then re-tie the end tip knot.

Zippers

A worn slider is the cause of most zipper problems. An occasional application of 303™ Protectant or a silicone-based lubricant will help reduce wear. Grit accelerates slider wear. Keep zippers clean by rinsing them under water after use in windy/sandy environments. Sometimes, carefully squeezing the top ends of the slider with a pair of pliers will restore some life. If an inner door slider fails, run it as far as possible toward one end of the zipper, and use only the other slider for the duration of the trip. A sewing repair shop can replace inoperable sliders.